



Sustainable Solutions for Health, Productivity and the Environment.



# PRS Water Damage PreClean



# PRS Water Damage PreClean

## Where to Use

PRS Water Damage PreClean is a biologically based initial treatment for water damage claims, especially category 3 (black water). It digests odors and soils, including those from fecal matter and urine, reducing them to water and carbon dioxide. PRS Water Damage PreClean utilizes spore strains and advanced cleaning technology specifically engineered for water damage claims. It is also designed for areas of heavy pet urine and soils from trauma.

### Benefits

- Non Toxic
- Biologically Based
- No Hazardous Ingredients
- Highly Concentrated

### Description

PRS Water Damage PreClean can help achieve timely and productive results for restoration professionals in water damage. This product will work from the moment you arrive until removal of enough water during the cleaning process limits its biological activity. It also eliminates the worst odors from water and category 3 (black water) damage shortly after application. Conventional odor control is not required. Do not introduce any non-PRS chemistry while PRS Water Damage products are at work. Apply as soon as possible.

PRS Water Damage PreClean eliminates odors within the location, liquefies solids in black water, starts the organic digestion process in all areas of sustained moisture, and minimizes odors within clean up equipment used by the contractor (i.e. wet vacs etc.). In the event of a 'Major Cat' PRS Water Damage PreClean can be used as a 'stop-gap' to control odors and soil load until a cleanup crew is available.

### Directions for Use

Shake well before use. Do not use below 50°F.

#### Standing category 3 (black water)/heavy load:

Apply 2 gallons PRS Water Damage PreClean per 400 sq. ft per one foot depth. (1 gallon/1500 gallons of black water) (3.8 litres/5700 litres).

**Standing category 3 (black water)/moderate load:** Apply 1 gallon (3.8 litres) PRS Water Damage PreClean per 400 sq. ft per one foot depth (or 1 gallon/3000 gallons of black water) (3.8 litres/11,400 litres).

### Distributor Contact Info

**Dried or Moist Load:** Dilute 1 gallon (3.8 litres) PRS Water Damage-PreClean with at least 1 gallon (3.8 litres) of water. For example, fill a 2 gallon pump up sprayer with 1 gallon (3.8 litres) of product and at least 1 gallon of water. Apply until contained area is visibly wet. Reapply as required to maintain visible wetness. Depending on the surface and drying conditions, a 2 gallon pump up sprayer will cover 1000 sq ft.

Perform physical cleanup as per IICRC S-500 guidelines. Extract residual, remove contents, carpets etc. depending on class of contamination.

Clean/pressure clean all surfaces and then apply PRS Water Damage Post Clean as per guidelines. Start your drying process as soon as possible.

Properties	
Color	Opaque White
Fragrance	Mild
Viscosity	Like Water
pH (concentrated)	7.0 (+/-0.5)
Phosphate Free	Yes
Biodegradable	Yes

Available Packages	Package Code	
55 gallon (1040 Litres) drum	# 11905257	
4x1 gallon (4x3.8 Litres) case	# 11905227	

For handling and precautionary information, reference the product label and safety data sheet.

To learn about our Professional Restoration Series please call 1.800.836.1633 or visit us at [www.rochestermidland.com](http://www.rochestermidland.com)