



XTRACT melamine floor pad

PRODUCT SPECIFICATIONS

4.0 Construction

This product is made of melamine foam laminated to a 100% recycled polyester nonwoven material and will not be affected by water or neutral cleaners.

5.0 Labeling

Labeling is to clearly identify product, size, and quantity. Americo brand and private label is available for this product.

6.0 Directions for use

- The incredible cleaning properties of melamine foam create an unusually high level of friction when introduced to the floor. It is important to add water, a neutral cleaning solution or a degreaser to both the floor pad and to the floor in order to reduce friction upon startup
- Apply non woven pad driver side of melamine floor pad to floor cleaning machine, white melamine side facing down toward floor
- Be sure to check machine pressure to avoid premature wear of pad
- Avoid rough uneven surfaces which can wear out pad quickly

7.0 Product Care

To prolong life of this product avoid rough uneven surfaces, always check machine pressure on pad, make sure pad and floor are always wet. Always saturate pad and floor before use.

8.0 Sizes

Round	Rectangular	Utility Pad
13"	12" x 18"	4.5" x 10"
14"	14" x 20"	
16"	14" x 24"	
17"	14" x 28"	
20"	14" x 32"	

Other sizes available by request

9.0 Sustainability

- The XTRACT Melamine Floor Pad does not require the use of harsh chemicals
- Laminated nonwoven material is made with 100% recycled post-consumer polyester fibers

10.0 Equipment

Best suited for standard speed machines: both single disc, oscillating and automatic scrubber.

1.0 Description

This pad is made using the original BASF opencell melamine foam, laminated to nonwoven material made of 100% recycled polyester fibers. The melamine pad works miraculously to clean floors without removing the floor finish. It is mainly used on shallow grouted floors, cleaning any heavily soiled floors, and is excellent for removing stubborn black marks.

2.0 Properties

Property	Value
White Foam	100% open-cell melamine foam
Brown Nonwoven Backing	Made of 100% recycled PET polyester fiber
Thickness	0.9" Total (Melamine 0.6" /Nonwoven 0.3")
Weight	40 osy
Pack	5 per case

3.0 Use

This product is used for cleaning and restoring a variety of flooring: LVT (Luxury Vinyl Tile), VCT (Vinyl Composite Tile), Terrazzo, Ceramic and Porcelain Tiles,

Epoxy or Concrete Flooring. Ideal for use on machines up to 350 rpm.

Americo Manufacturing Company, Inc. 1-800-241-9902

www.americomfg.com

★ 2022 Rev. 6/13/2022 Xiract Melamine Floor Pad Product Specifications Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact Americo with any questions or concerns.