

High-Powered Concrete and Tile Cleaner and Degreaser/Booster Additive

HydraBoost CT is a powdered, high-powered concrete and tile and grout cleaner and degreaser designed to safely and effectively dissolve, break down, dislodge, and emulsify even the grimiest soils from concrete, finished concrete, and ceramic, porcelain, and quarry tile floors and surfaces.

**Hydra Master** 



If for any reason you are not thrilled with the performance of HydraBoost CT, return it to your distributor and we'll get you a product that does.

6.5 Pounds (2.95 Kg)

designed to penetrate porous surfaces and dissolve the toughest build-up of oil and grease. Alkaline cleaning agents and heavy duty surfactants are activated by the power of oxygen to allow the effervescent solution to get into every crack, crevice, and pore. It is the ideal cleaning agent for heavily soiled restaurant kitchen tile floors and other indoor and outdoor surfaces exposed to high levels of grease and oil contamination. It does so without the use of harsh chlorinated solvents or mineral spirits, leaving the surface squeaky clean and residue free. HydraBoost CT is specifically designed to work in conjunction with high powered hard surface cleaning wands such as the RX-20 with hard floor attachments, and rotary or stationary hard surface cleaning extraction wands. Its powerful formula though, will work with virtually any brush agitation system, automatic floor scrubber, or even a mop and bucket cleaning system. HydraBoost CT is designed to be used as a preconditioning agent and applied to the surface being cleaned first. The oxygenated cleaning power of HydraBoost CT also makes it an ideal boosting agent for trashed and neglected carpet that has been exposed to high levels of oxygenated oils and grease. Simply add a couple of ounces of **HydraBoost CT** to your favorite traffic lane cleaner/ preconditioner for the ultimate in cleaning power.

**HydraBoost CT** is a powdered, high-powered concrete

even the grimiest soils from concrete, finished concrete,

and ceramic, porcelain, and quarry tile floors and surfaces.

HydraBoost CT is an economical cleaner and degreaser

and tile and grout cleaner and degreaser designed to safely

and effectively dissolve, break down, dislodge, and emulsify

### Directions:

- Read entire label before using. Use only as directed. Always pretest surface with cleaning solution for color¬fastness prior to cleaning. Ensure work area is wellventilated during application. Keep children and pets out of the area during application and drying. HydraBoost CT is not recommended for cleaning natural stone floors.
- This product is ultra-concentrated. For normal soiling: mix 2 ounces of HydraBoost CT powder with 1 gallon of warm or hot water into a professional sprayer. For extreme soiling: mix 3 to 4 ounces of powder with 1 gallon of warm of hot water into a professional sprayer. For application through a in-line injection sprayer: mix 12 oz. of powder and fill container with water. Use 4:1 dilution.
- Apply mixed solution with sprayer evenly and liberally across surface to be cleaned. You can use a pump-up sprayer or a battery powered sprayer. If preferred, you can apply mixed solution with a damp mop, sponge, or other appropriate professional equipment. If using a mop for solution application and surface cleaning, change your mop water often to make sure that soil is not re-deposited
- Allow for 5 -10 minutes of dwell time. For concrete, if stains have been deeply absorbed, allow 15 minutes of dwell time so the solution has time to reach into the concrete pores and crevices and the oxygen activated effervescent solution can dissolve the soiling and lighten discoloration.

- 5. For best results, agitate and extract cleaning solution using warm or hot water and a rotary agitation hard surface cleaner such as a the **RX-20** with hard floor attachments, or rotary or stationary hard surface cleaning extraction wands For tight spaces or especially sensitive surfaces, use a hard surface cleaning wand, or simply mop to rinse with clean warm or hot
- When area has been rinsed thoroughly. Allow floor to dry.
- For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after

## For use as a carpet cleaning solution booster/additive:

- Mix 2 ounces of HydraBoost CT with each gallon of mixed prespray (traffic lane cleaner, preconditioner) solution. This mixture is not recommended for wool carpeting or residential nylon carpets that are being properly maintained.
- Always pretest surface with boosted cleaning solution for color¬fastness prior to cleaning.
- Proceed to apply the pre-spray and continue cleaning in accordance with the directions of the pre-spray.

Contents: Sodiun carbonate (497-19-8), sodium percarbonate (15630-89-4), trisodium phosphate (10101-89-4), sodium metasilicate (6834-92-0), alcohol ethoxylate (68439-46-3) d-limonene (5989-27-5), proprietary surfactant, proprietary

sequestrant.

# GHS U.S. - CLASSIFICATION: WARNING

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

## PRECAUTIONARY STATEMENTS (GHS-US)

The product is classified and labeled according to the Globally Harmonized System (GHS)

If medical advice is needed, have product container or label at hand Keep out of reach of children. Read label before use.

Wash skin and contaminated clothing thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear suitable protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water.

■ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

If eve irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/ international regulations.

CLASSIFICATION SYSTEM: NFPA/HMIS Definitions: 0-Least, 1-Slight. 2-Moderate, 3-High, 4-Extreme,

■ NFPA RATINGS (SCALE 0-4): Health = 2. Fire = 0. Reactivity = 0. ■ HMIS RATINGS (SCALE 0-5): Health = 2. Fire = 0. Reactivity = 0



See Safety Data Sheet (SDS): scan here or visit www.hvdramaster.com for additional safety and regulatory information.

Part # 950-782-S Art 950-782-S R2

HvdraMaster 11015 47th Avenue West Mukilteo, WA 98275 425.775.7272



www.HydraMaster.com